

IR-2106/301

EXTENDED AREA BLACKBODY



6" x 6"
5 to 150 °C

Specifications:

Temperature Range:	5 to 150 C
Emittance Watts/Cm² (Watts):	.17 (5.4)
Wavelength Range:	1-99 um
Emissivity:	0.96 +/- 0.02
Emitter Size: in (mm)	6" x 6" (152.4 x 152.4)
Source Type:	Extended Area
Temperature Resolution:	0.1 C
Calibration Accuracy:	+/- 0.2 C to NIST Standard
Stability: Short (Long) Term:	+/- 0.1 C (+/- 0.2C)
Response Time:	Ambient – Max <20 Min
Temperature Sensors:	Platinum RTD & Type T
Control Type:	Active Multi-Band P.I.D.
Line Voltage:	90 to 125 or 208-240 VAC 50-60 Hz
Power Requirements:	200 Watts Max
Cable Length:	8 Feet (2.4 m)
Dimensions: in (mm) Source:	8" H x 8" D x 8" W (203.2x203.2x203.2)
Controller:	5.1"H x 13.4"D x 12"W (130x340x304)
Warranty:	1 Year
Standard Apertures:	6" x 6" (152.4 x 152.4)
Remote Interface:	RS-232, RS-485 or IEEE-488/GPIB

Infrared Systems Development introduces a NEW Low-Cost 6" x 6" Thermo-Electrically cooled / Heated blackbody source with a temperature range of 5°C to 150°C. The solid Copper Emitter plate provides superior uniformity and energy emission. Our Proprietary High Emissivity Black Coating provides >0.95 uniform Emissivity from 0.8 to 30 um. A Type "T" Thermocouple is embedded in the emitter plate to allow independent monitoring and calibration of the surface temperature. The IR-2106 offers maximum reliability, stability and uniformity comparable to those of competitive systems, but at less than half the cost, providing the best cost to performance ratio.

7319 SANDSCOVE CT. #4 Φ WINTER PARK, FL 32792
(TEL) 407-679-5101 Φ (FAX) 407-679-5520

SALES@INFRAREDSYSTEMS.COM [HTTP://WWW.INFRAREDSYSTEMS.COM](http://WWW.INFRAREDSYSTEMS.COM)

IR-2106/301 DIMENSIONS

